Package: snc (via r-universe)

October 8, 2026

Type Package

Title Strongest Neighbor Coherence

Version 0.1.0

Maintainer Kevin E. Wells <kevin.e.wells@usm.edu>

Description Computes Strongest Neighbor Coherence (SNC), a structural diagnostic that replaces Cronbach's alpha using top-k correlation structure.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Imports stats

Suggests knitr, rmarkdown

VignetteBuilder knitr

Repository https://theotherdrwells.r-universe.dev

Date/Publication 2025-07-09 20:17:38 UTC

RemoteUrl https://github.com/theotherdrwells/snc

RemoteRef HEAD

RemoteSha d995a9d2622d23916bfeaf17d23ec88d42e1a935

Contents

print.snc 2
snc 2

Index **4**

print.snc *Print Method for SNC Objects*

Description

Prints summary output for an object of class "snc".

Usage

```
## S3 method for class 'snc'
print(x, ...)
```

Arguments

x	An object of class "snc" returned by the snc function.
...	Ignored.

snc *Strongest Neighbor Coherence (SNC)*

Description

Computes Strongest Neighbor Coherence (SNC), a rotation-free structural diagnostic that evaluates how well each item aligns with its top-k most strongly correlated neighbors.

Usage

```
snc(R, k = 2, factors = NULL, digits = 3)
```

Arguments

R	A square item correlation matrix (symmetric, 1s on the diagonal).
k	Integer. Number of strongest neighbors to use for each item (default = 2).
factors	Optional. A vector of factor assignments for items, used to compute group-level means.
digits	Number of decimal places to round to (default = 3).

Value

An object of class "snc" with:

overall Mean SNC value across all items

items A data frame of item-level SNC values

factors (Optional) A data frame of factor-level mean SNC values

Examples

```
R <- matrix(c(1, .6, .3, .6, 1, .5, .3, .5, 1), 3, 3)
rownames(R) <- colnames(R) <- c("Item1", "Item2", "Item3")
snc(R)
```

Index

print.snc, 2

snc, 2, *2*